

INDUSTRIELL LØSNING PARAMETERE

Eksempel på gjerde med overligger.

Høyde. C/C stolper. Start/ende stolpe. Hjørnestolpe. Mellomstolpe. Overligger. Netting

1000	2500	T/L 50x50x5	L 50x50x5	T 50x50x5	L 50x50x5	50x50/2,7mm
1200	2500	T/L 50x50x5	L 50x50x5	T 50x50x5	L 50x50x5	50x50/2,7mm
1500	2500	T/L 60x60x6	L 60x60x6	T 50x50x6	L 50x50x5	50x50/2,7mm
1800	2500	T/L 60x60x6	L 60x60x6	T 50x50x6	L 50x50x5	50x50/2,7mm
2000	2500	T/L 60x60x6	L 60x60x6	T 50x50x6	L 50x50x5	50x50/2,7mm
2500	2500	T/L 60x60x6	L 60x60x6	T 50x50x6	L 50x50x5	50x50/2,7mm
3000	2500	T/L 60x60x6	L 60x60x6	T 50x50x6	L 50x50x5	50x50/2,7mm

Eksempel på gjerde uten overligger.

Høyde. C/C stolper. Start/ende stolpe. Hjørnestolpe. Mellomstolpe. Skråstiver. Netting

1000	2500	T/L 50x50x5	L 50x50x5	T 50x50x5	L 50x50x5	50x50/2,7mm
1200	2500	T/L 50x50x5	L 50x50x5	T 50x50x5	L 50x50x5	50x50/2,7mm
1500	2500	T/L 60x60x6	L 60x60x6	T 50x50x6	L 50x50x5	50x50/2,7mm
1800	2500	T/L 60x60x6	L 60x60x6	T 50x50x6	L 50x50x5	50x50/2,7mm
2000	2500	T/L 60x60x6	L 60x60x6	T 50x50x6	L 50x50x5	50x50/2,7mm
2500	2500	T/L 60x60x6	L 60x60x6	T 50x50x6	L 50x50x5	50x50/2,7mm
3000	2500	T/L 60x60x6	L 60x60x6	T 50x50x6	L 50x50x5	50x50/2,7mm

Andre parametere på forespørsel.